

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 August 2005 (11.08.2005)

PCT

(10) International Publication Number
WO 2005/072872 A1

(51) International Patent Classification⁷: **B01L 3/00**

INGANÄS, Mats [SE/SE]; Lapplandsresan 14, S-757 55 Uppsala (SE). THORSEN, Gunnar [SE/SE]; Höstgatan 24, S-126 37 Hägersten (SE).

(21) International Application Number:
PCT/SE2005/000114

(74) Agent: BERGANDER, Håkan; Gyros AB, Uppsala Science Park, S-751 83 Uppsala (SE).

(22) International Filing Date: 31 January 2005 (31.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0400181-4 29 January 2004 (29.01.2004) SE
60/540,262 29 January 2004 (29.01.2004) US

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US): GYROS AB [SE/SE]; Uppsala Science Park, S-751 83 Uppsala (SE).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

(72) Inventors; and

(75) Inventors/Applicants (for US only): ENGSTRÖM, Johan [SE/SE]; Artillerigatan 12B, S-752 37 Uppsala (SE).

[Continued on next page]

(54) Title: FLOW PATHS COMPRISING ONE OR TWO POROUS BEDS



(57) Abstract: A microfluidic device that comprises a microchannel structure in which there are one, two or more flow paths (101;202a,b;302a,a',b) all of which comprises a porous bed I (104,204,304) that is common for all of the flow paths and exposes an immobilized reactant R that is capable of interacting with a solute S that passes through the bed. The characteristics are that at least one of the flow paths comprises/comprise a second porous bed II (105,205,305) that is placed upstream to porous bed I (104,204,304) and is dummy with respect to interaction with solute S but capable of interacting with a substance DS that is present in a liquid aliquot together with solute S and is capable of disturbing the result of the interaction between solute S and said immobilized reactant R. There is also disclosed a method utilizing the device and variant of the device in which the immobilized R is replaced with a generic affinity ligand L₁, and/or porous bed II exposes a generic ligand L_{II} that may be different from L₁.

WO 2005/072872 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*